



## SRv6

Technology and Deployment Update

Mounir Mohamed
Systems Architect – Global SP Team

### Thank you

- Lead operators
- EcoSystem Partners
- Academic and Open-Source Partners
- IETF Partners
- Cisco SR Team




#### segment-routing.net

- SRv6 uSID: <u>CKN</u>, <u>MPLS WC</u>, <u>DKNOG</u>, <u>Training</u>
- SRv6 Ultra-Scale SR Policy: 26 uSID push at linerate: demo
- BGP PIC Edge with SRv6 Summarization: ISIS UPA: demo
- Path Tracing: <u>NANOG</u>, <u>Tutorial</u>

© 2022 Cisco and/or its affiliates. All rights reserved. Cisco Public

## Introduction

#### **Transparent Services**



- Customer packet is encapsulated from ingress to egress of the SR Domain
- SRv6 is applied to the OUTER header
- The inner packet is untouched

- Unified control-plane data-plane E2E
- Native inter-domain routing with optimal ECMP
- Native core and DC integration


{Mac, IPv4, IPv6}

#### SRv6 Network Programming - RFC8986

- The End-to-End Policy is encoded as a Network Program
  - The first instruction is in the outer DA
  - The remaining instructions are in the SRH
- An instruction (a SID) may be bound to any behavior
  - TILFA FRR and uLoop Avoidance
  - Traffic Engineering: internal to the domain and across peering links
  - L2/L3 VPN's
  - NFV
  - Any HW custom behavior: P4 on Silicon1
  - Any SW custom behavior: Container orchestrated by Kubernetes
- Powerful Service Creation
  - Any service can be encoded as an ordered list of instructions (Low-latency Slice, VPN, NFV)
- Stateless-Fabric
  - The state (Network program) is in the header

#### **SR Extension Header**

- SRv6 is a native extension of IPv6
  - RFC 8754
  - As foreseen 25 years ago by RFC2460
- SRH contains an ordered list of SID's




### Unified Data Plane And Seamless Deployment

- A unified data plane spanning from Application socket to Internet peering though Datacenter, Access, Metro, Core, Peering
- A single data plane natively supported by all nodes – just IP!
- Seamless forwarding through IPv6 transit nodes
- Most use-cases do not need an SRH
  - DA SID contains up to 6 micro-instructions (uSID's)



### SRv6 Solves Many Challenges



- 1000 times less IGP routes than with MPLS
- No BGP inter-AS Option A/B/C
- End-to-End Flex Algo Continuity



#### More on SRv6

- Cisco Knowledge Network "SRv6 Standardization Deployed at Scale"
  - https://www.segment-routing.net/tutorials/2021-11-18-CKN-SRv6/

# **Deployment Status**

#### Record-Speed Deployment

- 3 years of commercial deployment (2019-2022)
- ~100M SRv6 subscribers
- ~100 deployments, with ~14 public reports
- Across markets (Web, SP, Enterprise) and geographies (Asia, EU, US)

SoftBank	Rakuten	Indosat	MTN Uganda	Noia
lliad	Alibaba	China Telecom	China Bank	Cernet2
Free	Bell Canada	China Unicom	Line	

#### Commitment to SR Lead-Operators



Standard-Based Technology



Vendor eco-system



Open-Source eco-system

#### **Mature Standardization**

- Proposed Standard
  - RFC 8402 SR Architecture
  - RFC 8754 SRv6 DataPlane
  - RFC 8986 SRv6 Network Programming
  - RFC 9252 SRv6 BGP Extension
  - RFC 9256 SR Policy
  - RFC 9259 SRv6 OAM

Much faster standardization than usual

Sign of the SRv6 Industry Endorsement

### Rich SRv6 Ecosystem

#### **Network Equipment Manufacturers**













#### Merchant Silicon









#### **Open-Source Applications**



















#### **Open-Source Networking Stacks**















#### **Smart NIC**





#### **Partners**

















**Segment Routing** 

v6



#### Many Successful Interops

- 2020/04: EANTC: SRv6 interop between Cisco, Huawei, Juniper, Arrcus, Ixia (link)
  - Classic IPv6 nodes as SRv6 transit nodes
  - SRv6-L3VPN for IPv4 and IPv6 services
  - SRv6 TI-LFA FRR link protection with SRH insert
  - SRv6 EVPN for E-Line and EVPN L3VPN services
  - SRv6 TE SR Policy
- 2021/02: NetOne Systems (link)
  - · Cisco XR, Cisco NX, Juniper
- 2021/09: EANTC: SRv6 interop between Cisco, Huawei, Juniper, Nokia, Spirent (<u>link</u>)
  - SRv6-Based Global IPv4 and IPv6 services
  - SRv6-L3VPN for IPv4 and IPv6 services
  - SRv6 TI-LFA FRR local SRLG protection with SRH insert
  - SRv6 EVPN for E-Line and EVPN L3VPN services
  - IGP Flex-Algo using TWAMP-measured link delays

## SRv6 uSIDs

#### SRv6 uSID Terminology

- Industry:
  - SRv6 Micro Segment
  - SRv6 uSID
  - Briefly: uSID
- IETF: NEXT-C-SID
  - Briefly: Next
  - IETF document: draft-ietf-spring-srv6-srh-compression-01
  - Training: link

#### Container of 6 uSID's

- SRv6 Network Programming (RFC8986)
  - The source encodes any end-to-end program as an ordered list of instructions
  - The first instruction is in the outer DA
  - The remaining instructions are in the SRH
- An instruction is called a SID
- A Container SID may contain up to 6 micro-instructions called uSID's


FC00:0000:1111:2222:3333:4444:5555:6666

uSID Block uSID1 uSID2 uSID3 uSID4 uSID5 uSID6

#### Perfect SRv6 Integration

- uSID reuses SRH (RFC8754) without any change
- uSID strictly applies the SRv6 Network Programming (RFC8986)
- uSID can be bound to any Network Programming Instruction

### SRv6 uSID offers the best SRv6 Compression



#### SRv6 uSID in Deployments

#### Rakuten – SRv6 uSID in Deployment



- 5G End-to-End Network Slicing based on SRv6 uSID Flex-Algo
  - SRv6 uSIDs are allocated from the ULA address range
  - SRv6 uSID ISIS Flex-Algo: Low-Cost vs Low-Delay
  - SRv6 uSID BGP services
  - SRv6 uSID TII FA
  - Cisco NCS5500 and NCS-540 series
- Innovation in partnership with Cisco
  - BGP PIC Core and Edge with SRv6 Summarization: ISIS UPA (demo)
  - SR BW counters for deterministic and scalable capacity planning and BW guarantee

https://www.segment-routing.net/conferences/MPLS-WC-2022-Amit-Dhamija/

#### Bell Canada - SRv6 uSID Deployment



- · Bell promptly switched from SR-MPLS to SRv6 uSID
- Continued Simplification (remove MPLS dataplane)
- · Better Routing Scale: Summarization
- · Better HW Scale: linerate 26 uSID push for end-to-end SR Policy
- · Seamless Deployment (6 uSID's in DA without SRH)
- · End-to-End IP Unified Dataplane from socket to Internet Peering
  - SRv6-TE Policy: topological and service uSID's
- · Service Programming
- Reduce network service costs by up to 90% footprint by 75% power consumption by as much as 66%

https://www.segment-routing.net/conferences/MPLS-WC-2022-Daniel-Voyer/

https://www.segment-routing.net/conferences/MPLS-WC-2022-Daniel-Bernier-Jesper-Eriksson/

#### SRv6 uSID - Rich Eco-System

CISCO

· Cisco, NoviFlow, Arrcus, Nokia, Ciena



• Merchant: Silicon One, Broadcom, Marvell, Barefoot



• Open Source: Linux, FD.io, P4, eBPF, Cillium, SAI, SONIC, FRR

















#### More on uSID

- SRv6 Technology Status and Deployment Update
  - <a href="https://www.segment-routing.net/conferences/MPLS-WC-2022-Clarence-Filsfils/">https://www.segment-routing.net/conferences/MPLS-WC-2022-Clarence-Filsfils/</a>

# Path Tracing

### The exact path from A to M is not known

• 7 possible "valid" ECMP path


- ABFM, ABGM, ACFM, ACGM, ACHM, ADGM, ADHM ...

ABFM, ABGM, ACFM, ACGM, ACHM, ADGM, ADHM ...

ABFM, ABGM, ACFM, ACGM, ACHM, ADGM, ADHM ...


#### The exact path from A to M is not known

- 7 possible "valid" ECMP path
  - ABFM, ABGM, ACFM, ACGM, ACHM, ADGM,
     ADHM ...
- What exact path was taken by one specific packet?
  - 40-year-old unsolved IP problem
  - Packet may have also taken an invalid path (Routing or FIB corruptions)
- Timestamp at each hop
- Interface Load at each hop




#### The Path Tracing Idea


- Stamping in the packet header
- Implemented at linerate in the most basic HW pipeline
  - Reports true packet experience
  - No punting to CPU, no offload to co-processors
- Ultra-MTU-efficient
  - Highly compressed for low MTU overhead
  - Only 3 bytes per hop (12bit interface, 8bit TS, 4bit load)
- Each transit router records:
  - · Outgoing interface ID
  - Timestamp
  - Outgoing interface Load
- Native interworking with legacy nodes
  - Seamless deployment




### Stamping Trajectory in PT Header



### Stamping Trajectory in PT Header




### Stamping Trajectory in PT Header



### Minimize HW complexity by leveraging SDN analytics

- Exact path validation (interface by interface)
  - detect blackholes
  - detect unexpected paths
  - detect missing paths
- Propagation latency & Optical stability
- Per node jitter measurement



#### Ecosystem

illiilli cisco

- Cisco Shipping in CY22
  - C8000 (Q200), NCS5700 (J2), ASR9000 (LS)
- Rich Eco-System
  - Cisco, Broadcom, Marvell, +others
- Rich Open-Source
  - Linux, FD.io VPP, P4, Wireshark, TCPDUMP















- Path Tracing is being standardized at IETF
  - Path Tracing in SRv6 networks (ietf.org)

#### Stay up-to-date



amzn.com/B01I58LSUO



amazon.com/dp/B07N13RDM9





twitter.com/SegmentRouting



segment-routing.net



facebook.com/SegmentRouting/



linkedin.com/groups/8266623



The bridge to possible